

Certificate Of Conformity to EN14960:2019

This certificate relates only to the individual product detailed below. It confirms that at
(R) the time of manufacture this product conforms to EN14960.

To remain compliant this product must be tested annually.

To book your test please call +44 (0)1179 414 918 or visit www.airquee.com for more information.

This is the test certificate for your new inflatable. Please keep this in a safe place. This is valid for one year from the date below.

Product: Tractor Combo **Serial No:** AQS48436 **Code:** AQ7707

Valid From: 19-03-2022 Certificate No: AQS48436

· · · · · · · · · · · · · · · · · · ·											
Product Dimensions (m)											
Н	W	L									
2.9	3.7	4.6									
User Height (m)											
1	1.25	1.5	1.8								
Number of Users											
6	5	4	4								

Certificate No: AQS48436					1	1.25	1.5	1.8	
Tag No: N/A							Number	of Users	
Weight: Unit: 83kg Total: 95kg				6	5	4	4		
	Structure	Pass	Fail	N/A	Not	es			
1	Security Of Seems	Х			Material : gloss 630g pvc, 520g printable				
2	Stitching	Х							
3	Anchor Points	Х			Anchor points: 7 pcs PVC & metal triangle Bottom				
4	Anchor Accessories	Х			Supplied anchor accessories: 7 pcs / 400 mm* 18 mm	metal pegs	5		
5	Walls & Towers	Х			Inside wall height: 1.10 m				
6	Blower Tube(s) / Valve(s)	Х			Blower tube length: 1.47 m Position: 1 pcs r	ear side			
7	Zip(s)	Х			Zips: 1 pcs (exterior velcro flap + interior non return f	lap)			
8	Fabric Flame Retardant	Х							
9	Fabric Strength	Х							
10	Step / Ramp Size	Х			Platform height: 0.66 m Step depth: 1.17 n	n			
11	Grounding	Х							
12	Sharp Angles	Х							
	Stability	Х							
	Ropes			Х					
	Artwork	Х			Artwork : printed + laminated uv				
16	Air Loss Points	Х			1				
	Water Gauge Pressure (WGP) / Pressure (mbar)	Х			WGP: 5.4 inch /13.45 mbar				
	Fall Off Height (FOH)	Х			FOH: 0.45 m				
	Trough Depth	Х							
	Thread	Х							
	Netting	Х			Netting: black scrim fixed Roof : red gloss 45	0a PVC			
	Entrapment	Х				5			
	Deflation / Evacuation Time	Х							
	Windows	X							
	Markings	X							
	Identification	X							
Totally Enclosed Structures				Not	es				
27	Exits			Х					
	Exit Markings			Х					
	Lighting Supports			X					
	Emergency Lighting			Х					
	Deflation Speed			Х					
	User Area Pressure			Х					
Slides			Not	es					
33	Wall Height / Platform Height	Х			Wall height: 0.55 m Platform height: 1.45 m				
	Run-Out	X			Run out: 0.9 m				
	Clamber Step	X			Width of slide: 0.75 m				
	Slide Sheet	X			Slide sheet: bright green sliding material PVC				
Blower		Not	es						
37	Size & Type	Х			Blower power: 1 pcs 1.5HP				
	Inlet & Outlet Mesh	X	\vdash	\neg	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2				
	Cable & Plug	X	\vdash	$\neg \neg$					
	Casing & Impeller	X	\vdash	$\neg \neg$					
	Pat Test		\vdash	X					
	Return Flap	Х	\vdash						
			\vdash						

SIGNED BY: Edina RPII ANNUAL INFLATABLE INSPECTOR Airquee Ltd

dah

Date of test: 19-03-2022

Airquee Ltd Duel House Llandowlais Street Cwmbran NP44 7XB, UK

Tel:+44 (0)1179 414 918 **Email:** sales@airquee.co.uk





To remain compliant this product must be tested annually.