

Certificate Of Conformity to EN14960-1:2019

This certificate relates only to the individual product detailed below. It confirms that at the time of manufacture this product conforms to EN14960. To remain compliant this product must be tested annually.



To book your test please call +44 (0)1179 414 918 or visit www.airquee.com for more information.

Product: 15 x 12ft 3D Christmas Front Slide Combi

Serial/Certificate no:
AQ69797

Code: AQ8398

Tag No: N/A

Valid From: 22-10-2025

Weight: Unit: 92kg Total: 104kg

Structure	Pass	Fail	N/A
Trough Depth	X		
Seam Security	X		
Stitching	X		
Walls & Towers	X		
Can Walls Contain Users	X		
Fall Off Height (FOH)	X		
Grounding	X		
Stability	X		
Entrapment	X		
Sharp Angles	X		
Zip(s)	X		
Windows			X
Netting	X		
Clamber Netting			X
Air Loss Points	X		
Markings	X		
Artwork	X		
Identification	X		

Materials	Pass	Fail	N/A
Fabric Material and Condition	X		
Thread Condition	X		
Material Fire Retardancy	X		
De-lamination of PVC	X		

Anchorage	Pass	Fail	N/A
Total No of Anchors	X		
Anchor Point Integrity	X		
Anchor Point Location	X		
Anchor Type	X		
Anchor Accessories	X		
Ropes			X

Blower	Pass	Fail	N/A
Kilopascal (kPa)	X		
Size & Type	X		
Inlet & Outlet Mesh	X		
Cable & Plug	X		
Casing & Impeller	X		
Pat Test			X
Return Flap	X		
Blower Tube(s) / Valve(s)	X		

Entrances, Exits & Evacuation	Pass	Fail	N/A
Deflation / Evacuation Time	X		
Length of Step	X		

Totally Enclosed Structures	Pass	Fail	N/A
Exits			X
Exit Markings			X
Lighting Supports			X
Emergency Lighting			X
Deflation Speed			X
User Area Pressure			X

Slides	Pass	Fail	N/A
Wall Height / Platform Height	X		
Run-Out	X		
Clamber Step	X		
Slide Sheet	X		

Notes
Indoor Use Only: No Label Location: side Length: 4.65m Width: 3.7m Height: 3.10m Bed width panel: 0.55 Trough depth: 0.11 Inside wall height: 1.05 m FOH: 0.47 m Grounding weight: 85 Zips: 1 pcs (exterior velcro flap + interior non return flap) Netting: black scrim fixed Roof : red gloss 450g PVC Artwork : printed (laminated, UV resistant)

Notes
Material : gloss 630g pvc + 520 g printable material

Notes
Calculated Anchors: 6 Anchor points: 8 pcs PVC & metal triangle Bottom Supplied anchor accessories: 8 pcs / 400 mm* 18 mm metal pegs

Notes
kPa: 1.22 Blower minimum pressure: 1.00 Blower power: 1 pcs 1.5HP Blower tube length: 1.23 m Position: 1 pcs rear side

Notes
Evacuation time(secs): 20 Enclosed Unit: Yes Platform height : 0.66m Step Length: 1.20m

Notes

Notes
Platform wall height: 0.72 Platform wall height 1st metre: 0.56 Platform roof fitted: Yes Wall height: 0.56 m Platform height: 1.42 m Run out: 1 m Width of slide: 0.72 m Slide sheet: red sliding material PVC

Users

Max User Height: 1.8	Max Users upto 1m: 6	Max Users upto 1.25m: 5	Max Users upto 1.5m: 4	Max Users over 1.8: 4
----------------------	----------------------	-------------------------	------------------------	-----------------------

SIGNED BY: Oláh Etele Tibor
PIPA ANNUAL INFLATABLE INSPECTOR

