

Certificate Of Conformity to EN14960:2019

This certificate relates only to the individual product detailed below. It confirms that at the time of manufacture this product conforms to EN14960.
To remain compliant this product must be tested annually.

To book your test please call +44 (0)1179 414 918 or visit www.airqueue.com for more information.

Product: Safari Multiplay 5.5 x 5.0m

Serial No: AQS53449

Code: AQ8571

Valid From: 13-02-2023

Certificate No: AQS53449

Tag No: N/A

Weight: Unit: 136kg Total: 150kg

| Product Dimensions (m) | | | |
|------------------------|------|-----|-----|
| H | W | L | |
| 3.9 | 4.8 | 5.5 | |
| User Height (m) | | | |
| 1 | 1.25 | 1.5 | 1.8 |
| Number of Users | | | |
| 8 | 7 | 6 | 5 |

Structure

| | Pass | Fail | N/A |
|--------------------------------|------|------|-----|
| 1 Security Of Seams | X | | |
| 2 Stitching | X | | |
| 3 Anchor Points | X | | |
| 4 Anchor Accessories | X | | |
| 5 Walls & Towers | X | | |
| 6 Blower Tube(s) / Valve(s) | X | | |
| 7 Zip(s) | X | | |
| 8 Fabric Flame Retardant | X | | |
| 9 Fabric Strength | X | | |
| 10 Step / Ramp Size | X | | |
| 11 Grounding | X | | |
| 12 Sharp Angles | X | | |
| 13 Stability | X | | |
| 14 Ropes | | | X |
| 15 Artwork | X | | |
| 16 Air Loss Points | X | | |
| 17 Kilopascal (kPa) | X | | |
| 18 Fall Off Height (FOH) | X | | |
| 19 Trough Depth | X | | |
| 20 Thread | X | | |
| 21 Netting | X | | |
| 22 Entrapment | X | | |
| 23 Deflation / Evacuation Time | X | | |
| 24 Windows | X | | |
| 25 Markings | X | | |
| 26 Identification | X | | |

Totally Enclosed Structures

| | | | |
|-----------------------|--|--|---|
| 27 Exits | | | X |
| 28 Exit Markings | | | X |
| 29 Lighting Supports | | | X |
| 30 Emergency Lighting | | | X |
| 31 Deflation Speed | | | X |
| 32 User Area Pressure | | | X |

Slides

| | | | |
|----------------------------------|---|--|--|
| 33 Wall Height / Platform Height | X | | |
| 34 Run-Out | X | | |
| 35 Clamber Step | X | | |
| 36 Slide Sheet | X | | |

Blower

| | | | |
|------------------------|---|--|---|
| 37 Size & Type | X | | |
| 38 Inlet & Outlet Mesh | X | | |
| 39 Cable & Plug | X | | |
| 40 Casing & Impeller | X | | |
| 41 Pat Test | | | X |
| 42 Return Flap | X | | |

Notes

Material : gloss 630g pvc + gloss 520g printable

Anchor points: 10 pcs PVC & metal triangle Bottom
Supplied anchor accessories: 10 pcs / 400 mm* 18 mm metal pegs
Inside wall height: 2.10 m
Blower tube length: 1.47 m Position: 1 pcs rear side
Zips: 2 pcs (exterior velcro flap + interior non return flap)

Platform height : 0.53 m

Artwork : printed

kPa: 1.16
FOH: 0.58 m

Netting: Yes Roof : black scrim fixed

Notes

Notes

Platform height: 1.6 m
Run out: 2.00 m
Width of slide: 1.2 m
Slide sheet: yellow sliding material PVC

Notes


Blower power: 1 pcs 1.5HP

SIGNED BY: Demeter Attila
RPII ANNUAL INFLATABLE INSPECTOR

Demeter Attila

Date of test: 09-02-2023

Airqueue Ltd
Duel House
Llandowlais Street
Cwmbran
NP44 7XB, UK
Tel: +44 (0)1179 414 918
Email: sales@airqueue.co.uk



To remain compliant this product must be tested annually.