

Certificate Of Conformity to EN14960:2019

This certificate relates only to the individual product detailed below. It confirms that at (R) the time of manufacture this product conforms to EN14960. To remain compliant this product must be tested annually.

To book your test please call +44 (0)1179 414 918 or visit www.airquee.com for more information.

Product: 12 x 10 A Frame PJ Mask

Code: AQ5971PJ Valid From: 14-03-2024 Certificate No: AOS58810

Serial No: AQS58810

| | Product Dimensions (m) | | | | | | | | | | | | |
|---------------|------------------------|------|------|-----|--|--|--|--|--|--|--|--|--|
| | Н | W | L | | | | | | | | | | |
| | 2.9 | 3.1 | 3.85 | | | | | | | | | | |
| | User Height (m) | | | | | | | | | | | | |
| | 1 | 1.25 | 1.5 | 1.8 | | | | | | | | | |
| | Number of Users | | | | | | | | | | | | |
| | 4 | 3 | 2 | 2 | | | | | | | | | |
| Notes | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| mm metal pegs | | | | | | | | | | | | | |
| C: | cs rear side | | | | | | | | | | | | |

| | Certificate No: AQS5881 | .0 | | | | 1 | 1.25 | 1.5 | 1.8 |
|--------------------------------|-------------------------------|------------------|------|-----|---|--------------|--------|----------|-----|
| Tag No: N/A | | | | | | | Number | of Users | |
| Weight: Unit: 50kg Total: 60kg | | | | | 4 | 3 | 2 | 2 | |
| | Structure | Pass | Fail | N/A | No | tes | | | |
| 1 | Security Of Seems | Х | | | Material : gloss 630g pvc + gloss 520g printable | | | | |
| 2 | Stitching | Х | | | | | | | |
| | Anchor Points | Х | | | Anchor points: 6 pcs PVC & metal triangle Bottom | | | | |
| 4 | Anchor Accessories | Х | | | Supplied anchor accessories: 6 pcs / 400 mm* 18 mm | n metal pegs | ; | | |
| | Walls & Towers | Х | | | Inside wall height: 1.05 m | | | | |
| | Blower Tube(s) / Valve(s) | Х | | | Blower tube length: 1.47 m Position: 1 pcs | rear side | | | |
| | Zip(s) | Х | | | Zips: 1 pcs (exterior velcro flap + interior non return | | | | |
| | Fabric Flame Retardant | Х | | | | | | | |
| | Fabric Strength | Х | | | | | | | |
| | Step / Ramp Size | X | | | Platform height : 0.68 m Step depth : 1.15 | m | | | |
| | Grounding | X | | | Step deptil 1 2125 | ••• | | | |
| | Sharp Angles | X | | | | | | | |
| | Stability | X | | | | | | | |
| | Ropes | ^ | | Х | | | | | |
| | Artwork | Х | | | Artwork : printed (laminated, UV resistant) | | | | |
| | Air Loss Points | X | | | Artwork : printed (laminated, ov resistant) | | | | |
| | Kilopascal (kPa) | $\frac{1}{x}$ | | | kPa: 1.44 | | | | |
| | Fall Off Height (FOH) | X | | | FOH: 0.48 m | | | | |
| | | X | | | FOR. 0.46 III | | | | |
| | Trough Depth | X | | | | | | | |
| | Thread | - | | | Nothing his decided fixed | FO D\/C | | | |
| | Netting | X | | | Netting: black scrim fixed Roof : red gloss 4 | 50g PVC | | | |
| | Entrapment | Х | | | | | | | |
| | Deflation / Evacuation Time | Х | | | | | | | |
| | Windows | Х | | | | | | | |
| | Markings | Х | | | | | | | |
| 26 | Identification | Х | | | | | | | |
| Totally Enclosed Structures | | | No | tes | | | | | |
| | Exits | | | Х | | | | | |
| | Exit Markings | | | Х | | | | | |
| | Lighting Supports | | | Х | | | | | |
| | Emergency Lighting | | | Х | | | | | |
| 31 | Deflation Speed | | | Х | | | | | |
| 32 | User Area Pressure | | | Χ | | | | | |
| Slides | | No | tes | | | | | | |
| 33 | Wall Height / Platform Height | | | Х | | | | | |
| 34 | Run-Out | | | Х | | | | | |
| 35 | Clamber Step | | | Х | | | | | |
| 36 | Slide Sheet | | | Х | Slide sheet: N/A | | | | |
| Blower | | Notes | | | | | | | |
| 37 | Size & Type | Х | | | Blower power: 1 pcs 1.5HP | | | | |
| 38 | Inlet & Outlet Mesh | Х | | | | | | | |
| 39 | Cable & Plug | Х | | | | | | | |
| 40 | Casing & Impeller | Х | | | | | | | |
| 41 | Pat Test | | | Х | | | | | |
| 42 | Return Flap | Х | | | | | | | |
| | | | | | | | | | |


SIGNED BY: Oláh Etele Tibor PIPA ANNUAL INFLATABLE INSPECTOR Airquee Ltd

Date of test: 15-03-2024

Duel House Llandowlais Street Cwmbran NP44 7XB, UK

Tel:+44 (0)1179 414 918 Email:sales@airquee.co.uk





To remain compliant this product must be tested annually.